

Gas Leak Detector



Gas Electronic Leak Detector LD239

An electronic leak detector is indispensable for finding small leaks around fittings or hot inlets on which a liquid cannot be used. Leak check solutions may contain material that can leak into the gas-supply lines or columns and cause ghost peaks or other contamination.

The LD239 leak detector uses a small pump to pull air from the probe through a thermal-conductivity cell. The presence of carrier gas or Hydrogen changes the thermal conductivity and causes a change in the detector's readout compared to a reference air flow.

- Super Compact and Light (only 95 g)
- LCD and LED Displays
- Highly Sensitive – 0.0005 ml/min (He)
- USB Port Rechargeable

The world's smallest leak detector with MEMS technology!



Specifications:

Detection method:	Thermal conductivity
Target gases:	Helium, Hydrogen, CO ₂ , Argon, Neon and other non-corrosive gases. For safety reasons, LD239 should not be used: 1) in places with a risk of fire, explosion or large flammable gas leaks; 2) in places with insufficient ventilation when attempting to detect trace amounts of flammable gases; 3) in places that are contaminated with dust or combustible fumes.
Sensitivity:	Standard range - minimum 0.005 ml/min (He) High range - minimum 0.0005 ml/min (He)
Settings:	Sensitivity Range: (Standard/High), Buzzer: ON/OFF, LED Display: ON/OFF LCD Backlight: ON/OFF, Auto power shutdown: ON/OFF
Temperature range:	10 - 40°C (non-condensing)
Battery:	Rechargeable Lithium ion battery (up to five hours continuous use). Battery is rechargeable through USB port (2.5 hours for a full recharge).
Dimension:	50(W) x 19.5(D) x 111(H) mm
Weight:	Approx. 95 g
Accessories:	USB cable, instruction manual, AC-DC adaptor with EURO or UK plug (optional).

Part number information:


	P/No
Gas Leak Detector LD239 (ready to use)	2702-19340

Accessories:

Battery for LD239	2702-19341
AC-DC Adaptor, w/o Plug (USB, 5V, 500 mA)	G400006
Input Plug AC-DC Adaptor, EURO	G200010
Input Plug AC-DC Adaptor, UK	G200011
USB cable	2702-19331
Sample Filter	2702-19333



Distributed by:



MZ-Analysentechnik GmbH
Wöhlerstraße 2-6 • D-55120 Mainz
Tel +49 6131 68 66 19
Fax +49 6131 68 66 20
e-mail: info@mz-at.de
www.mz-at.de

GL Sciences B.V.
De Sleutel 9
5652 AS Eindhoven
The Netherlands
Tel. + 31 (0)40 254 95 31
E-mail: info@glsciences.eu
Website: www.glsciences.eu